EVALUATION OF STREAM CHANNELIZATION AND MITIGATION ON THE FISHERY RESOURCES OF THE ST. REGIS RIVER, MONTANA

by
John A. Lund
Cooperative Fishery Research Unit
Montana State University
Bozeman, Montana 59715

Contract No. 14-16-0008-737

Prepared for

OFFICE OF BIOLOGICAL SERVICES U.S. Department of Interior Fish and Wildlife Service Washington, D.C. 20240

# Biological Services Program

FWS/OBS-76/06 June 1976

# Evaluation of Channelization and Mitigation

On the Fishery Resources of the St. Regis River, Montana

FISH DIVISION

MONTANA FISH & GAME DEPT.

FILLINA, MONTANA 55001



Fish and Wildlife Service
U.S. Department of the Interior

The Office of Biological Services was established in FY'75 within the Fish and Wildlife Service to:

Support research, studies, and planning directed toward critical environmental issues

Develop improved ecosystem data for use in resource development actions

Provide needed authoritative ecological input for Department of Interior programs

Projects of the Biological Services Program are designed to strengthen the Fish and Wildlife Service's ability to predict and accurately assess the impact of land and water developments on fish and wildlife to enhance planned natural resource exploitation.

Current efforts are directed toward five major areas of environmental impact concern related to land and water use and resource development planning, decision making, and operations:

Coastal ecosystems including the Outer Continental Shelf Western energy development and related land and water use Stream alterations and wetlands

Power plant siting, operations, and related delivery systems

Development of habitat classification, evaluation, inventory and information systems

This report is an outcome from one of numerous contractual Research and Development efforts conducted on initial FY'75 funding. Your comments regarding its usefulness and your suggestions of additional similar information needs are encouraged and may be directed to:

Information Transfer Specialist National Stream Alteration Team U.S. Fish and Wildlife Service Route 1 Columbia, Missouri 65201 The opinions expressed in this report are those of the authors and not necessarily those of the Office of Biological Services, Fish and Wildlife Service. Any mention of commercial products does not imply endorsement by this agency.

# CONTENTS

		Page
Abst	ract	ii
List	of Figures	iii
List	of Tables	iv
Ackno	owledgements	v
Sect:	ions	
I	Conclusion	1
II	Recommendations	3
III	Introduction	5
IV	Methods	8
V	Results	11
VI	Discussion	37
VII	References	39
VIII	Appendix	41

### ABSTRACT

Stream morphology and gamefish populations of the St. Regis River,
Montana were studied during the summers of 1973, 1974 and 1975 to
determine the effects of stream channelization caused by highway
(Interstate 90 and U.S. 10) and railroad construction. In-stream
structures used to mitigate fish losses were also evaluated. Population
estimates were made using electrofishing methods on unaltered, altered,
altered with mitigating structures and "old" altered study sections.
Physical parameters of each section were mapped to show differences
between altered and unaltered sections.

Results of the study show that mitigating structures (jetties and random rock clusters) were effective in providing fish habitat comparable to unaltered sections. Fish populations in new channels usually stabilized in approximately one year. Trout populations in "old" altered sections with no mitigation failed to recover to unaltered section levels. Due to aesthetic reasons, fishermen preferred unaltered or partially altered section over altered sections. The number of pools per section as measured by pool-riffle periodicity provided the closest correlation to trout population changes.

This report was submitted in fulfillment of contract no. 14-16-0008-737 by the Montana Cooperative Fishery Research Unit under the sponsorship of the Office of Biological Services, Fish and Wildlife Service. Work was completed as of June 1, 1976.

# FIGURES

No.		Page
1.	Map of study area, showing location of study sections and zones.	7
2.	Average trout standing crop in kg/1000 m for all sections, 1973-1975.	29
3.	Gamefish standing crops in kg/1000 m for all sections in 1975.	31

#### TABLES

No		Page
1.	Types and Amounts (in Percent) of Alterations Present in Altered Study Sections as Measured in 1975.	12
2.	Summary of Physical Parameters Collected on all Study Sections from 1973-1975.	15
3.	Summary of Pool-Riffle Periodicity, Sinuosity, and Gradient Measurements on all Sections from 1973-1975.	17
4.	Percent of Stream Bottom Surface Covered by Each of Seven Size Classes (by Average Diameter) for Study Sections of the St. Regis River Taken in 1974 and 1975.	19
5.	Estimated Fish Cover by Location and Types Measured in 17 Study Sections of the St. Regis River in 1974 and 1975.	20
6.	Range and Average Minimum-Maximum Temperatures from Three Recording Stations on the St. Regis River During the Summers of 1974 and 1975.	22
7.	Measurements of Selected Chemical and Physical Properties Taken at Varying Water Flows During 1974 and 1975.	23
8.	Summary of Discharge Measurements (in m <sup>3</sup> /s) Taken on the St. REgis River, 1973-1975.	25
9.	Estimated Average Fish Population for all Sections Electro- fished in 1973, 1974 and 1975.	27
10.	Estimated Fishing Pressure Observed on the St. Regis River for two Periods During the Summers of 1974 and 1975.	35
11.	Estimated Number and Biomass of Gamefish per 1000 Meters of Stream in Each Section of the St. Regis River in 1973, 1974 and 1975.	4.2
- 4	17/4 and 17/J.	42
12.	Estimated Population and Average Length by Age Groups Given for years 1973-1975.	

### ACKNOWLEDGEMENTS

The author wishes to extend his gratitude to all who helped in the course of this study. Dr. Richard J. Graham and Mr. Rodney Berg initiated the project and gathered the first year's data. Dr. William R. Gould headed the study for part of 1974. Dr. Richard W. Gregory directed the project and helped prepare the quarterly and final reports.

The U.S. Forest Service, Lolo National Forest, provided aerial photographs of the river and lodging for the crew. Mr. Gordon Haugan, U.S. Forest Service biologist, was especially helpful in supplying background material and in planning the study.

Mr. Barry Schaplow, graduate student, and the student technicians were instrumental in gathering the data.

Dr. Norman G. Benson, National Stream Alteration Team Project Officer, provided guidance and critically reviewed the Manuscript.

The project was financed by the Office of Biological Services, Fish and Wildlife Service, under contract number 14-16-0008-737.

# SECTION I CONCLUSIONS

The results of this study indicate that mitigating structures in altered channels of the St. Regis River have been effective in providing fish habitat comparable to the unaltered sections.

Channel structures produced stream bottom contours similar to those found in unaltered sections.

Where mitigating structures failed during high water (section2), trout populations (biomass and fish greater than 18 cm) were significantly lower than in the unaltered control.

Gamefish populations in altered sections with mitigation recovered from construction work in about one year.

Erosion and turbidity caused during channel construction and the initial unstable channel bottom were of relatively short duration and seemed to have no long-term effects on the biology of downstream areas. New channels usually stabilized after one high-water period.

Changes in water temperature and water chemistry due to channel alterations were not detected.

Trout populations in "old" altered sections (more than 50 years old) with no mitigation failed to recover to unaltered section levels.

Properly constructed jetties and random rock clusters of large riprap material produced good, economical trout habitat.

Fishermen favored unaltered or partially altered stream sections, compared to altered sections, probably for aesthetic reasons.

The following problems associated with channelization were not alleviated: (1) loss of stream bank vegetation, (2) destruction of the natural stream aesthetics, and (3) loss of stream length in most cases.

# SECTION II RECOMMENDATIONS

Implementation of the following recommendations should help mitigate habitat losses due to channelizations along high gradient trout streams like the St. Regis River.

- Alter original stream channels only when absolutely necessary, and then keep alterations to a minimum. When a lengthy channelization occurs, meander the new channel as much as possible to correct ditchlike appearance and to retain original stream length.
- 2. Vegetation (especially trees and shrubs) along new channels should be retained, if possible, to provide bank stability and shade. When top-soil and vegetation are lost, banks should be sloped and topsoil replaced and reseeded down to the high-water mark. Trees and shrubs such as red dogwood, willow, common chokecherry, alder and birch should be planted along stabilized stream banks.
- 3. When riprap is needed to hold the stream in a new channel, it should be covered with subsoil and topsoil down to high-water mark and then revegetated with grass, trees and shrubs.
- 4. Jetties, random rock clusters and other in-stream devices used to create pools must be properly engineered to withstand the annual high-water and the occasional floods wich occur. If riprap material is used to construct mitigating devices, it must be large enough to prevent hydraulic water pressure from spreading it out and burying it.
- 5. In gravel-bottomed streams, jetties and other mitigating devices should be placed 5-7 stream widths apart (alternating from each streambank) to

match pool-riffle and meander sequences found in unaltered sections.

- 6. Mitigating structures must be placed in the currents close to thalweg to be most effective in providing trout habitat.
- 7. Random rock clusters and jetties could be used together (cluster near outer end of jetty) to create larger mid-channel pools.

# SECTION III INTRODUCTION

## **GENERAL**

Stream alteration and channelization projects have generally benn considered as detrimental to fish and wildlife populations in the disturbed areas. The reduction of both warm water and cold water fish populations by stream alteration has been documented by several authors, including Alvord and Peters<sup>1</sup>, Elser<sup>2</sup>, Irizarry<sup>3</sup>, Congdon<sup>4</sup> and Tarplee, Louder and Weber<sup>5</sup>. Populations of gamefish were depleted as much as 95% in these studies. Efforts to improve trout habitat in stream has met with varying degrees of success. Hunt<sup>6</sup> and Shetter, Clark and Hazzard<sup>7</sup> have shown good success in improving brook trout populations in two unaltered streams. Latta<sup>8</sup> had only marginal success in improving brook and brown trout populations in a Michigan stream. Trout populations in a channelized section of the Weber River, Utah were restored to unaltered levels by various channel structures (Barton, White, Winger and Peters<sup>9</sup>).

# **OBJECTIVES**

The major objectives of this study were to determine the effects of channel alterations and rehabilitation measures in channelized areas on the cold water sport fisheries of the St. Regis River. The study included:

(1) a comparison of physical, biological and chemical characteristics of "old" and "newly" altered areas with those of unaltered areas; (2) a determination of the overall effectiveness of mitigating devices in restoring fish habitat; (3) making recommendations for mitigating biological losses from future stream alterations.

# DESCRIPTION OF AREA


The St. Regis Eiver is located in the mountains of northwestern Montana just east of the Idaho-Montana border. It flows southeasterly for about 63 km

(39 miles) to its confluence with the Clark Fork River near St. Regis, Montana (Figure 1). The elevation of the river ranges from 1707 m (5600 ft) to 805 m (2640 ft) msl. Average discharge recorded at the USGS gaging station near St. Regis (drainage area = 785 Km) was 15.9 m/s (562 cfs) for a 15-year period ending in 1973. The maximum recorded discharge of 312 m<sup>3</sup>/s (11,000 cfs) occurred during a flood on May 19, 1954, and a minimum discharge of 1.2 m<sup>3</sup>/s (41 cfs) on December 30, 1968. Average stream width is about 13 meters, but varies greatly from the headwaters to the mouth.

The river flows through a narrow valley and is paralleled by U.S. Highway 10 and a railroad for most of its length. In 1962, approximately 68 percent of the stream length received some degree of channel alteration (Alvord and Peters<sup>1</sup>). Most of the alterations were due to highway and railroad construction projects which straightened and riprapped the river in many areas. Approximately 8 km of channel were relocated resulting in the loss of 1.5 km of stream length. The construction of Interstate 90 has resulted in additional channelization and relocation sites because of the canyon's narrow areas and constrictions of the river caused by the railroad and Highway 10 grades.

The following species of gamefish were found to be present in the river during the study: rainbow trout (Salmo gairdneri), cutthroat trout (Salmo clarki), brown trout (Salmo trutta), brook trout (Salvelinus fontinalis, dolly varden trout (Salvelinus malma) and mountain whitefish (Prosopium williamsoni). Cutthroat trout and brook trout were the major species in the upper half of the river. Mountain whitefish, rainbow trout and brown trout were the major species in the lower half.

Nongame species present included longnose sucker (Catostomus catostomus), largescale sucker (Catostomus macrocheilus) and slimy sculpin (Cottus cognatus). Only a few of the two sucker species were found in the lower half of the river, while sculpin was common the full length of the river.



Map of study area, showing location of study sections and zones. Figure 1.

# SECTION IV

## GENERAL

The river between Borax Springs and the mouth was divided into five zones based primarily on discharge changes resulting from the entrance of the larger tributaries. Sixteen study sections were selected from highway construction plans and by onsite inspection so the various altered and unaltered channel types could be included. Comparison of fish populations were generally made between sections within each zone.

## CHANNEL MAPPING

All study sections were mapped at least once during the three years of the study (1973-1975). Study sections averaged 831 m in length, ranging from 361-1518 m. Measurements were taken during the usual low flow period (late August - early September) each year. Transects were taken at regular intervals (3-15 m apart) across each section, but never at an interval wider than the average width (water edge to water edge) of the section. Measurements taken at each transect included channel width, water depth, fish cover, bottom materials, and thalweg velocity. Depths were recorded at 0.6 m (2 ft) intervals when the channel was less than 12 m (40 ft) wide and at 1.2 m (4 ft) intervals when the channel width was greater than Islands and large rocks were excluded in computing average depth. Thalweg velocities were measured at the deepest point along the transect using a Teledyne Gurley meter adjusted (0.6 from the surface) to measure the average volocity. The type of bottom materials present was estimated by observations through a plastic viewer (30.5 cm in diameter) at regular intervals (approx. 60 readings/section). Pools were defined as areas having depths equal to or greater than one standard deviation of the average thalweg depth for the section. Pools were usually denoted by lower thalweg velocities (usually less than 0.5 m/s). Gradients were calculated for each section using a surveyor's transient and rod. Discharge measurements were taken at 7 stations using standard USGS techniques. Temperature readings were also taken during the summers at three stations using Taylor thermographs.

Fish cover was measured in 1974 and 1975 along transects placed at 15-24 m intervals. All cover 1.5 cm (5 ft) on either side of the transect line was measured. The total area of fish cover provided by overhanging brush, debris, roch shelves, and undercut banks was recorded. The cover was classified as being submerged, 0-60 cm, 60-150 cm, or greater than 150 cm above the water. The total fish cover mapped in each section varied from 20 percent in the shortest section to 12 percent in the longest section.

# POPULATION ESTIMATES

The fish population of each section was sampled using a 1500 w, 110 volt A.C. generator and 0-400 volt D.C. rectifier unit. The electrofishing gear was usually operated from a small flat-bottomed boat. Captured fish were anesthetized with MS-222 (Tricane methanesulfonate), weighed, measured, finclipped, and redistributed throughout the section. Blocking nets were placed at the lower end of each section (mostly in 1975) prior to each electrofishing operation. The mark and recapture method for making population estimates was used. Usually one or two mark and/or recapture trips were required per section. A period of at least 24 hours was allowed to elapse between mark and recapture runs.

The Bailey modification of the Petersen estimator (formula 3.7 in Ricker 10) was used to estimate the population of each major species in each section. Number and biomass estimates were made by length and age groups using a computer program developed by the Montana Fish and Game Department. The computer program also provided 80% confidence limits on all condition factors of fish over 13 cm (5 inches) and on all population estimates. The gamefish populations of each section were tested against other sections in the zone to determine if population numbers and/or weights were significantly different. Trout populations were not considered significantly different if the 80% confidence intervals were overlapping.

# FISHERMAN SURVEYS

Fishing pressure counts were made during the summers of 1974 and 1975. Counts were made by driving along the river between section one and St. Regis and counting the number of people fishing. Census days and hours were randomly selected without replacement. At least one weekend day each week and all holidays were included. A creel survey was also conducted in 1975 to determine hourly catch rates, species composition, and fishing methods. Interviews were conducted after each pressure count trip and at the end of the day to get as many completed fishing trips as possible.

# SECTION V RESULTS

## STREAM MORPHOLOGY

Five types of stream habitats were studied. These were classified as partially altered (PA), "old" altered (OA), "new" altered (NA), altered with mitigation (AM), and unaltered (UA). All stream habitat types were represented by at least two study sections.

# Lookout Zone

Four study sections were selected in zone I to represent habitat types found in this mountainous headwater area. Section 1 (PA) had 33 percent of its length altered during construction of I-90 (Table 1). Section 2 (AM) was relocated and channelized by I-90 construction, step dams were added for mitigation. Section 3 (UA) was the control section for zone 1. Section 4 (OA) was straightened by railroad construction over 50 years ago.

# Saltese Zone

Five study sections were selected in this "upper" canyon area of the river. Section 5 (UA) was used as a control section for zone II. This section was moved upstream 1.5 km to a more representative unaltered site in 1975. Section 6 (PA), (60 percent altered), was partly altered by old and recent highway construction, but retained some unaltered areas. Section 7 (AM) is a narrow, highly channelized section relocated by I-90 construction, random rocks were added for mitigation. Section 7A (NA) was added in 1975 because it was similar and adjacent to sections 7 and 8. Section 8 (AM) was relocated and straightened by I-90 construction (less gradient and wider than section 7), jetties were added to this section.

TYPES AND AMOUNTS (IN PERCENT) OF ALTERATIONS PRESENT IN ALTERED STUDY SECTION AS MEASURED IN 1975. TABLE 1.

				Se	Section Number	Numb	er	11542 1976						
	н	7	4	9	7	7.A	80	6	10	11	110	11L	17	13
Alterations			-		8		10			æ	P		- sats	
1. Riprap* "Old"	0	0	20	21	0	20	0	20	17	23	0	0	07	38
"New"	25	61	0	26	100	10	100	0	0	0	34	22	0	0
<ol> <li>Other changes</li> <li>(dikes,etc) +</li> </ol>	0	36	34	13	0	0	0	ဖ	11	0	0	0	12	0
3. Channel relocation	Д	ပ	بم	д	ပ	ρı	ပ	<u>.</u> A	ρ,	ρų	ρι	O	а	ы
Total Percent Altered	33	100	84	09	100	09	100	56	28	23	93	100	25	38
Percent of Unstable Banks	4	25	0	7		0	0	12	11	29	59	78	6	7
Mitigating Structures Added?	S <sub>N</sub>	Yes	No No	No	Yes	No No	Yes	No	No	No	N <sub>0</sub>	Yes	No	No
				3										

<sup>\* &</sup>quot;New" riprap = material placed during Interstate-90 construction; "Old" riprap = material placed along original highway and railroad grades.

# P = Partial Relocation, C = Complete Relocation

<sup>+</sup> Include contouring, diking and bridge abutments.

# Haugan-Riverside Zone

Five study sections were selected in this wide and flat portion of the drainage. Section 9 (OA) was altered by railroad construction over 50 years ago. Section 10 (PA) has two altered areas (28 percent of total) caused by railroad construction. Section 11 (PA) had one area of relocation and channelization (23 percent) before it was relocated to a new channel. Section 11U (NA) is the upper half of relocated section 11 which was moved in January 1975. Section 11L (AM) comprises most of the lower half of relocated section 11 and has jetties for mitigating structures. Section 11A (UA) was the downstream control section for zone III.

# Drexel Zone

Two study sections in the "lower" canyon area were added to provide data prior to I-90 construction. Section 12 (PA) was altered in several areas (52 percent) by Highway 10 and railroad encroachment. Section 13 (PA) was also altered (38 percent) by Highway 10 and railroad grades.

# St. Regis Zone

One study section was selected in this lower, flat portion of drainage. Section 14 (UA) is a low gradient section used as a control for sections 12 and 13. This section also provided baseline data before I-90 construction.

# Physical Parameters

Physical parameters obtained by mapping channels of study sections on the St. Regis River are shown in Table 2. The general trends shows average width, depth, thalweg depth and thalweg velocity increasing in a downstream direction. There were, however, some exceptions to this trend. Section 7 (AM) had a 30 percent loss of width compared to the section directly upstream. This was caused by the straightening and compressing of the section between the old highway and Interstate 90. Decreases in average depth and thalweg depth were noted for sections 7A (NA), 8 (AM), 9 (OA), 11U (NA), and 12 (PA).

A coefficient of variation (page 62, Snedecor and Cochran 11) was calculated for each parameter (Table 2) to measure the Variability of each section. By averaging the percent variations (average width, depth and thalweg depth), an overall variation for each section was obtained. Unaltered study sections (3, 5, 11A and 14) have a 51 percent variation average compared to 48 percent for partially altered sections (1, 6, 10, 11, 12 and 13), 48 percent for sections altered with mitigating structures (2, 7, 8 and 11L), 44 percent for "newly" altered sections (7A and 11U), and 30 percent for "old" altered sections (4 and 9). Percent variations from the mean depth and thalweg depths are directly related to the quantity and/or size of pools present in each section. The unaltered sections, since they have the highest average variations, appear to have one of the pre-requisites for good trout habitat, that being the highest number and/or sizes of pools. Altered sections with mitigating devices also had relatively high percent variations, as did the partially altered sections. "Old" altered sections without mitigation showed a low percent variation, indicating little or no recovery from channelization.

SUMMARY OF PHYSICAL PARAMETERS COLLECTED ON ALL STUDY SECTIONS FROM 1973-1975. (DATA ON SECTION 1, 2, 3, 4, 7, 8, 9 and 10 REPRESENT 2 YEAR AVERAGES, ALL OTHERS MAPPED ONLY ONCE). TABLE 2.

14	1518	3.20	21.1	39.5	79.0	75.0
13	1421 1455	3.02 3.03 3.20	21.3 20.8 21.1 (19) (29) (34)	27.5 32.4 39.5 (65) (65) (84)	54.9 61.1 79.0 (27) (24) (49)	63.4 59.4 75.0 (48) (49) (53)
12	1421	3.02	21.3 (19)	27.5 (65)	54.9 (27)	63.4 (48)
11A	1212	2.15	17.7 (26)	33.8 (89)	66.4 (48)	68.3
Ħ	1914	1.53 2.15	16.8 17.7 (26) (26)	33.6 (80)	67.3 (48)	74.9 (45)
110	914	1.56		22.9 (74)	49.9	58.7 64.9 69.8 71.0 (20) (43) (37) (38)
11	2217 914	3.46	15.6	29.3 (75)	28.5 46.9 53.5 49.9 (10) (58) (45) (32)	69.8 (37)
10 11	12 1	77.	16.2 (48)	22.3	46.9	64.9
6	36 8	.75 1	17.7 (11)	15.7	28.5 (10)	58.7
Section 8	361 436 876	0.42 0.44 0.75 1.44 3.46 1.56	6.8 10.0 12.3 17.7 16.2 15.6 17.0 (19) (19) (20) (11) (48) (28) (50)	25.1 24.6 16.6 15.7 22.3 29.3 22.9 (72) (61) (72) (57) (94) (75) (74)	33.3	58.4
Sec 7A		0.45 0	10.0	24.6 (61)	45.5 (26)	69.8
7	416 424	0.28	5.8 (19)	25.1 (72)	47.5	67.9 (44)
9	413			22.3	42.8 (40)	sec) 52.0 (46)
<b>*</b> Ω	997	87.0	10.2 (31)	20.9	43.9 (27)	y (cm/ 52.2 (50)
4	471	0.36	7.6 ]	15.5	m) 28.4 (18)	10c1t; 54.1 (39)
ဗ	th (m)	0.31	6.3 (23)	1 (CED)	veg (c 28.4 (35)	49.1 (43)
racteristic	lengt 475	ectare 0.21	width 4.4 (36)	depth 9.2 1 (87)	thalv 19.0 (42)	thalv 34.2 (56)
Characteristic	Section length (m) 480 475 486 471 466	Area (hectares) 0.22 0.21 0.31 0.36 0.48 0.40	Average width (m) +4.6 4.4 6.3 7.6 10.2 9.7 (C) (23) (36) (23) (20) (31) (28)	Average depth (cm) 10.7 9.2 13.8 15.5 20.9 22.3 (C) (84) (87) (87) (65) (72) (72)	Average thalweg (cm) 21.7 19.0 28.4 28.4 43.9 42.8 47.5 45.5 (C) (37) (42) (35) (18) (27) (40) (29) (26)	Average thalweg velocity (cm/sec) 35.3 34.2 49.1 54.1 52.2 52.0 67.9 69.8 58.4 (C) (51) (56) (43) (39) (50) (46) (44) (39) (38)

<sup>\*</sup> Data from "new" section 5 mapped in 1975 only.

<sup>+</sup> C = coefficient of variation as a % = (standard deviation/mean x 100)

A natural stream channel, whether nonmeandering (straight) of meandering usually has an undulating bed. According to Leopold, Wolman and Miller, "alternates along its length between deeps (pools) and shallows (riffles) at a repeating distance of 5 to 7 widths". This is true of all streams having bottom material larger than coarse sand. (Leopold, Wolman and Miller 12). Pool-riffle periodicity is the average distance between pools or riffles measured in average stream widths for the section. Ratios for this study (Table 3) were 6.0 for altered sections with mitigation, compared to 6.3 for un-altered sections, 8.0 for partially altered sections, 12.0 for altered sections without mitigation and 12.4 for "old" altered sections. The average ratio of 6.3 (range 4.6 to 7.7) for unaltered sections and 6.0 (4.1 to 9.3) for altered sections with mitigation compares favorably with 5 to 7 width figure stated above. The altered sections with no mitigating devices had little pool development as noted by the high pool-riffle ratios.

The thalweg, in natural stream conditions, also tends to move back and forth across the channel every 5 to 7 channel widths, even in straight reaches. The ratio of thalweg length to down valley distance (defined as sinuosity) is a measure of the relative degree of thalweg and channel meandering. The ratio of unaltered sections averaged 1.22, compared to 1.17 for partially altered sections, 1.15 for altered with mitigating structures, 1.11 for altered without mitigation and 1.05 for "old" altered sections (Table 3). Channelization and bank stabilization with riprap eliminates meanders and reduces thalweg movement in most cases. In altered sections, thalweg movement failed to return unless mitigating structures were used to deflect the current back and forth.

Channel gradients (Table 3) generally decreased in a downstream direction. The sharp increase in gradient at section 7 was partially due to loss of stream length during channelization of this area. Other variations from the trend appear to be due mainly to natural changes in the drainage.

SUMMARY OF POOL-RIFFLE PERIODICITY, SINUOSITY, AND GRADIENT MEASUREMENTS ON ALL SECTIONS FROM 1973-1975. TABLE 3.

Characteristic	eristi(	U	7 ×	: :: :::::::::::::::::::::::::::::::::	U.		Se	Section	es es	s <sub>2</sub>	÷ .	600 m	n, <sup>E</sup>	×	6	a <sup>2</sup>	
	2	m	4	*2	9	<b>'</b>	7A	7A 8	6	10	# <b>#</b>	110	111	11A	12	13	14
Section length (meters) 480 475 486 471	lengtl 475	ћ (me 486	ters) 471	997	413	416	424	361	436	361 436 876 2217	2217	914	914	1212	1421	1455	1518
Pool-riffle periodicity 8.2 9.3 7.7 12.5	ffle pe 9.3	eriod 7.7		9.4	9.8	4.6	6.1	4.1	12.2 8.3	ຕຸສ	6.7	6.7 17.9	6.1	5.7	φ • •	7.8	7.2
Thalweg length (meters) 501 502 536 481	lengtl 502	հ (me 536	ters) 481	532	667	478	473	406	457	876	2286	896	1037	1310	1518	1575	1607
Valley length (meters) 448 465 436 465	length 465	(met 436	ers) 465	409	386	905	422	358		432 748	2132	878	875	1075	1356	1387	1435
Sinuosity 1.12	ty + 1.08	1.23	1.03	uosity + 1.12 1.08 1.23 1.03 1.30 1.29	1.29	1.18	1.18 1.12	1.13	1.06	1.13 1.06 1.27 1.07	1.07	1.10		1.19 1.22	1.12	1.14	1.12
Gradient (%) 2.60 2.43 1.65 1.24 1.14 1.06	t (%) 2.43	1.65	1.24	1.14	1.06	1.48	1.48 0.91	0.91	0.67	0.91 0.67 0.91 0.61	0.61	0.72		0.61 0.54	0.43 0.62	0.62	0.38

<sup>\*</sup> Data from "new" section five, taken in 1975

<sup>+</sup> Sinuosity equals thalweg length divided by valley length

# Bed Material

Size classes of bed material at each study section are shown in Table 4. The average size of bed material in each section generally decreased in a downstream direction. Material greater than 7.5 cm (3 in. average diameter) ranged from 76 percent of total in section 1 and 3 to 48 percent in section 14. Section 7 had the highest amount (34 percent) of material over 30 cm (12 in). This was due to the placement of random rock clusters on the streambed to improve fish habitat. Sections 11A and 14 each had the highest average (8 percent) of fine material less than 0.3 cm (0.1 in). Although fine material increased in the lower sections, these areas were localized and did not prevent natural reproduction of fish.

# Fish cover

The amount, type and location of fish cover in each section is presented in Table 5. Submerged fish cover is considered the most important type because it provides both protection and a place to rest away from the main current. Since measurements were taken during the yearly low water period, submerged cover measured at that time is available to fish year around. Submerged fish cover ranged from a high average of 151 m2/1000 m for unaltered sections to a low of 40 m<sup>2</sup>/1000 m in the "old" altered sections (Table 5). Cover 0-60 cm above the water would be of greater importance during high water periods when it would be submerged. This type of cover (mostly overhanging brush, debris and rock ledges) ranged from a high average of 225 m<sup>2</sup>/1000 m for unaltered sections to a low of 30 m<sup>2</sup>/1000 m for altered sections with mitigating structures. Cover higher than 60 cm above the water (groups 3 and 4) provides only limited cover, if any, for trout. The latter two types may be of more value in providing shade. Most of the newly altered sections had no cover over 60 cm due to construction practices.

TABLE 4. PERCENT OF STREAM BOTTOM SURFACE COVERED BY EACH OF SEVEN SIZE CLASSES (BY AVERAGE DIAMETER) FOR STUDY SECTIONS OF THE ST. REGIS RIVER TAKEN IN 1974 and 1975.

							Coot ton	9	50	=				100	
							פנודה	į							
, 2	ო	4	'n	ဖ	7	7.A	<b>6</b>	6	10	110	111	11A	12	13	14
0	7	0	7	8	0	0	т.	0	0	0	0	Ħ	0	H	0
Boulders (>30 cms) 28 19	56	23	17	17	34	28	13	19	'n	97	10	10	13	19	12
Course rubble (15-30 cm) 24 23	28	24	56	12	20	28	25	21	19	24	23	12	13	15	14
Fine rubble (7.5-15 cm) 24 31	70	21	28	31	19	16	21	24	28	28	25	19	70	18	22
Coarse gravel (2.5-7.5 cm) 12 18	10	19	16	21	14	16	22	18	31	70	21	56	31	56	25
Fine gravel (0.3-2.5 cm) 9 8	#	6	13	14	10	6	12	15	14	12	14	14	19	16	19
Sand (<0.3 cm) 3 1	m	4	e	· m	က	က	9	m	m	9	7	80	4	2	8 01
100 100 100 100	100	0 100	100	0 100	0 10(	100 100	100	100	100	100	9	201	8	3	

ESTIMATED FISH COVER BY LOCATION AND TYPES MEASURED IN 17 STUDY SECTIONS OF THE ST. REGIS RIVER IN 1974 and 1975 (IN M<sup>2</sup>/1000 METERS). TABLE 5.

.L 11A 12 13 14	10 62 6 2 1 - 12 63 6 272 414 502
11A 12	3:1
11A	10 12 272
H	15 - 15 292
111	- 0 0 227
110	_ 0 175
9	11 11 1152
6	14 14 176
fon 8	1 0 0 0 1
Section 7A 8	33 - 33 231
_	0 0 3 157
v	- 0 0 413
'n	0 - 4 657
4	144
<u>ش</u>	5 5 5 5 5 7 8
. 8	57
н	241
Fish Cover	A. Overhanging brush B. Debris,rock ledges etc.+ Subtotal Total
	-ro

<sup>\*</sup> Includes undercut banks and shelves caused by water erosion.

<sup>+</sup> Includes debirs, rock ledges and crevices, dead trees and branches, stumps, and grass clumps.

### STREAM CHARACTERISTICS

# Stream Temperatures

Maximum-minimum temperature variations were recorded at three locations in 1974 and 1975 (Table 6). Temperature trends were similar at all stations during the periods the three thermographs were in operation. Average maximum and minimum temperature increased in a downstream direction both years. The average temperature (averaging maximum and minimum temperatures) at each station shows a 2.5°C increase between section 3 and 11 in 1974, and a 1.7°C increase in 1975. The average change between sections 11 and 14 was 0.8°C in both 1974 and 1975. Diurnal differences between average maximum and minimum temperatures (Table 6) at the Lookout, Haugen-Riverside and St. Regis stations were 4.3°, 4.2° and 4.5°C in 1974 and 4.4°, 4.2° and 4.5°C in 1975, respectively. The highest temperature recorded during the project was 19.3°C (66.7°F) at the St. Regis station on July 30, 1975. The lowest recorded temperature was 3.1°C (37.5°F) at the Lookout station on June 12, 1974.

Higher than normal daytime stream temperatures were suspected in the channelized areas: however, attempts to measure these changes were frustrated by the entrance of ground water. Summer stream temperatures appear to be favorable for all species of trout and whitefish present with maximum temperatures well below critical levels.

# Water Chemistry

The St. Regis River has been described as having a relatively low productivity compared to other mountain streams. Water samples taken at the start of zone 1 (station A) and at the end of each succeeding zone (Table 7) bear this out. Total alkalinity and hardness exceeds 50 ppm only during low water periods at station F. Nutrients (orthophosphate, nitrate and nitrite nitrogen) were also measured and found to be at low levels. Turbidity readings also remained low, except when channel alterations were being made above station D.

TABLE 6. RANGE AND AVERAGE MINIMUM-MAXIMUM TEMPERATURES FROM THREE RECORDING STATIONS ON THE ST. REGIS RIVER DURING THE SUMMERS OF 1974 AND 1975.

			Stations	
		Lookout (Sec.3)	Haugan-Riverside (Sec.11)	St. Regis (Sec. 14)
Elevation (m	eters	)		
		1170	951	817
Distance bet stations (k			21.5	5.9
(,,,				4
			June II - Sept. 17, 19	74
Ave. minimum		£ 7		
temperature			9.1 (4.7-11.9)	9.7
Range		(3.1-10.0)	(4.7-11.9)	(5.5-13.3)
Ave. maximum				
temperature			13.2	14.2
Range		(5.6-14.7)	(6.9-16.7)	(7.5–18.3)
			June 13 - Sept. 2, 197	75
7			4 T V 4	
Ave. minimum temperature	(00)	7.2	9.1	0.0
Range		(3.3-10.8)	(4.7-12.2)	9.9 (5.3-13.6)
wange		(3.3-10.0)	(4.7-12.2)	(3.3-13.0)
lve. maximum				
temperature			13.3	14.1
Range		(4.7-16.4)	(6.7–17.5)	(6.9-19.3)

MEASUREMENTS OF SELECTED CHEMICAL AND PHYSICAL PROPERTIES TAKEN AT VARYING WATER FLOWS DURING 1974 AND 1975. TABLE 7.

			Station			
			Range (average)	ge)		
Property *	A	æ	ပ	D	ध्य	Cžą
нd	6.9-7.2 (7.0)	7.0-7.3 (7.1)	6.9-7.4 (7.2)	6.8-7.2 (7.0)	7.0-7.4 (7.2)	7.1-7.5 (7.4)
Conductivity (K 25 C)	37–70 (55)	42-86 (66)	44-78 (62)	48-86	51-84 (76)	54-136 (98)
Total Hardness (as $ppm CaCO_3$ )	17–28 (22)	20–34 (26)	17–32 (25)	22–33 (27)	24-36 (30)	28-56 (40)
Total Alkalinity (as ppm $CaCO_3$ )	18-29 (23)	21–35 (27)	18-31 (25)	23-37 (28)	23-39 (31)	28-56 (41)
Orthophosphate (ppm)	0-0.24 (0.06)	0-0.10 (0.03)	0-0.10 (0.04)	0.0.08	0-0.11 (0.04)	0-0.09
Nitrite Nitrogen (ppb)	1.0-11.0 (5.4)	0.5-6.0 (4.4)	0.5-8.0 (5.2)	0.5-6.0 (3.8)	0.5-7.0 (4.8)	0.5-8.0 (5.3)
Nitrite + Nitrate (ppm)	0.05-0.11 (0.09)	0.03-0.22 (0.12)	0.05-0.15 (0.10)	0.06-0.14 (0.11)	0.04-0.15	0.06-0.17 (0.11)
Turbidity (J.T.U.)	0-1.6 (0.6)	0-1.5.	0-2.3 (1.0)	0-27.5 (7.1)	0.5-4.5 (1.2)	0.5-2.7 (1.2)

# Discharge Measurements

Discharge measurements were taken at seven stations on the St. Regis River in 1973, 1974 and 1975 (Table 8). The river shows a steady increase in flow from station 1 (Borax Springs, start of Section 1) to the USGS gage station (Figure 1). The river has a wide range of discharges during a normal year. Flows at station 1 are from 40 to 60 times greater during the runoff period than during the low water period. At the USGS station, discharge readings were 15 to 25 times greater during runoff than during the low flow period. A maximum discharge of 273 m³/s (9, 640 cfs) was recorded at the USGS gage station on January 16, 1974 (during a flood). The lowest USGS flow reading was 1.7 m³/s (60 cfs) recorded on September 12, 1973. The flood of January 1974 had a detrimental effect on the fish populations in the river. Besides displacing fish downstream, most of the redds of fall spawners (brook and brown trout, mountain whitefish) were destroyed.

TABLE 8. SUMMARY OF DISCHARGE MEASUREMENTS (IN M<sup>3</sup>/S) TAKEN ON THE ST. REGIS RIVER, 1973-1975.

			S	tations				USGS	
Date	1	2	3	4	5	6	7	Gage Station	
	(a)	.1 (17	12		V =	3 -			
Distance a	bove mo	utn (Km							
	52.3	45.9	41.1	28.3	25.9	13.7	2.4	1.6	
		ă.		1070	1				
				1973					
July 14-16				1.43	1.93			4.16	
Aug. 14-21		0.18	0.50	0.57	0.87			2.27	
Sept. 5						1.32	1.61		*
Oct. 16			0.46		1.08	1.77		2.49	
1000				1974					
				17/4					
June 11	3.70							91.70	
	0.55	1.64	3.03	4.64.	7.44	12.30		17.10	
Aug. 17	0.25	0.38	0.91	1.76	2.01	3.50		5.69	
Sept 15-17		0.24	0.48	0.75	1.44	2.37	3.04	3.60	
				1975					
				1713					
June 15	3.47							60.00	
July 15	0.58	1.41	2.23	4.16	6.10	9.93		13.60	
Aug. 15	0.17	0.42	0.88	1.35	1.98	3.30		4.84	
Sept 15	0.06	0.31	0.60	0.86	1.45	2.30	3.00		

### GAMEFISH POPULATION ESTIMATES

Population estimates by length groups (Table 11, Appendix) and by age groups (Table 12, Appendix) were made on most sections from 1973 to 1975. Petersen mark and recapture runs were made each summer from mid-July to early September. Each section, however, was electrofished during approximately the same period each year.

The estimated number of each trout species in each section was averaged over the 3-year period (Table 9). Estimated whitefish populations for each section in 1975 are also shown. The first length group for each species was adjusted to include all age  $\mathbf{I}^+$  fish. The largest fish taken for each species in each section formed the upper limit of the last length group.

# Lookout Zone

An average of point estimates for trout populations in zone I shows no significant difference between section 1 (PA), section 2 (AM), or section 3 (UA). In populations of these three sections however, were significantly higher (80 percent confidence level) that the population of section 4 (OA), exceeding it by as much as 100 percent (Table 9). The higher number of trout in section 2 was due to the large number of age I cutthroat found there in 1974 (Table 12, Appendix).

The number of trout greater than 18 cm (7 in) was significantly higher in sections 1 and 3 than in sections 2 and 4. The number of larger trout in section 3 was 2, 38 and 55 percent greater than in sections 1, 2, and 4, respectively.

A singificantly higher average biomass of trout (Figure 2) was also found in section 3 compared to the other sections in zone I. The average weight of trout in section 3 exceeded those of sections 1, 2, and 4 by 18, 32, and 63 percent, respectively. Estimated gamefish standing crops for each section in 1975 are shown in Figure 3. The small numbers and weight of whitefish found in zone I did not affect section comparisons.

(EXPRESSED AS NUMBER PER 1000 METERS WITH NUMBER OF FISH GREATER THAN 18 CM IN PARENTHESES. ESTIMATED AVERAGE FISH POPULATIONS FOR ALL SECTIONS ELECTROFISHED IN 1973, 1974 AND 1975. RB = RAINBOW TROUT, CT = CUTTHROAT TROUT, BB = BROOK TROUT, LL = BROWN TROUT, DV = DOLLY [CONFIDENCE INTERVALS AT 80% LEVEL]. VARDEN TROUT, WF = MOUNTAIN WHITEFISH) TABLE 9.

Total Gamefish	606 (101)	675 (77)	(111)	335 (80)		476 (116)	930 (136)	768 (232)	432 (139)	1424 (198)
WF*	(2)	4 (4)	10 (10)	15 (15)		39 (39)	44 (44)	91 (91)	52 (52)	50 (50)
Trout 18 cm)(±)	(78)	(72)	(115) (11)	(53)		(79) (20)	(264)	(155) (31)	(72) (23)	(201)
Total T (>than 1	604	<b>6</b> 71 (73)	650 (101)	320 (65)		437 (77)	886 (92)	677 (141)	380 (87)	1374 (148)
DQ	Zone I				Zone II					58.1 A
13				*		. "				
Species BB	134 (28)	125 (20)	210 (45)	180 (28)		106 (34)	<b>69</b> (30)	72 (23)	57 (33)	160 (37)
IJ	470 (71)	546 (53)	(95)	140 (37)		331 (43)	817 (62)	<b>6</b> 05 (118)	323 (54)	1214 (111)
Section RB	1. Partially altered	<ol> <li>Altered/stepdams added</li> </ol>	3. Unaltered control	4. "Old" altered		5. Unaltered control	6. Partially altered	7. Altered/random rocks added	7A. Altered +	8. Altered/jettles added

<sup>\*</sup> Mountain Whitefish estimates for 1975 only.

<sup>+</sup> Estimated in 1975 only.


<sup>±</sup> Estimated in 1973 only.

				ý	pecies.			12			
	'RB		CI	27	BB	TI.	DV	Total Trout (>than 18 cm	rout 18 cm) (±)	WF*	Total Gamefish
						Z	Zone III				
9. "Old"	"Old" altered		514 (44)		(07) 86			613 (84)	(161) (18)	2 (2)	615 (86)
. Parti	10. Partiall altered		332 (60)	5	157 (48)	6		489 (108)	(102)	39 (39)	528 (147)
. Parti	11. Partially altered ±	+1	50 (15)		L58 (56)	13 (10)		221 (81)	(58)	1	
11U. Altered	+	8 (7)	55 (37)	1004	54 (46)	(2)		119 (92)	(11)	225 (224)	344 (316)
11L Alte jett	Altered/ jetties added+ (	2 (1)	35 (22)		74 (42)	9 (9)		117 (71)	(18) (13)	221 (221)	338 (292)
11A. Unalter control	pə	3 (2)	35		105 (40)	24 (13) Zones	V & VI	167 (64)	(29)	190 (187)	357 (251)
12. Partíal altered	1y	69 (26)	28 (6)		62 (20)	31 (11)		195 (67)	(31)	204 (204)	399 (271)
<ol> <li>Partfal altered</li> </ol>	1y	108 (41)	(3)		6 (5)	21 (6)	33	145 (56)	(23)	170 (168)	315 (224)
14. Unalter control	eq	114 (22)	6(2)		46 (17)	93 (56)	4 (4)	263 (101)	(45)	<b>5</b> 3 (53)	316 (154)

Mountain whitefish estimates for 1975 only.

Estimated in 1975 only

Estimated in 1973 only.



Average trout standing crop in kg/1000 m for all sections, 1973-1975. (\*Significantly higher at 80% level) Tigure 2.


#### Saltese Zone

The highest average number of trout in zone II was found in sections 8 (AM). Numbers in this section exceeded those in section 5 (UA), section 6 (PA), section 7 (AM and section 9 (OA) by 214, 55, 102 and 124 percent, respectively, and were significantly higher in each case.

The number of trout greater than 18 cm in zone II was significantly higher in sections 7 and 8, compared to sections 5 6, and 9. Numbers in section 8 exceeded those in sections 5, 6, 7, and 9 by 92, 61, 5, and 76 percent, respectively.

The average trout standing crop was also higher in section 8 (Figure 2), exceeding section 7 (the closest section) by 43 percent. The addition of whitefish biomass (Figure 3) to the trout estimates in 1975 raised section 7 above section 8. Sections 7 and 8 were both significantly higher than sections 5, 6, 7A and 9.

Section 7A was added in 1975 as an "altered control" section for sections 7 and 8. The sections with mitigating structures (7 and 8) exceeded section 7A by 120 and 167 percent in total trout and by 173 and 251 percent, respectively, in trout greater than 18 cm (Table 11, Appendix). Section 9 was compared to zone II sections even though it has a higher stream flow. Section 9 is very close to zone II (Figure 1) and has a similar species composition.



Gamefish standing crops in kg/1000 m for all sections in 1975. (\*Significantly higher at 80% level) Figure 3.

## Haugan - Riverside Zone

In zone III, mountain whitefish became the dominant species in the river. Section 10 marked the upper limit of whitefish reproduction and separated the upper, predominantly trout, sections from the lower, predominantly whitefish, sections. Section 10 (partially altered) had the highest average number of trout, compared to section 11 (partially altered) and 11A (unaltered control). Whitefish numbers in section 11A were significantly higher than those of section 10.

There was no significant difference in trout biomass averages (Figure 2) for zone III. Total gamefish biomass in 1975, however, was significantly higher in sections 11A, 11L and 11U, as compared to section 10 (Figure 3).

The recovery of fish populations in sections 11L (AM) and 11U (NA) were evaluated in 1975 after the stream had been relocated there from section 11. The two new sections had recovered 53 and 54 percent of these trout numbers in a 7-month period. The numbers of trout greater than 18 cm was not significantly different among the three sections. Whitefish in sections 11L and 11U had also reached levels equivalent to that of section 11A in both numbers and biomass (Table 9 and Figure 3). Section 11A had a 4 and 9 percent higher gamefish biomass than sections 11L and 11U, respectively, in 1975.

## Drexel and St. Regis Zones

Baseline population estimates were made in the Drexel and St. Regis zones prior to the start of I-90 construction in this area. Post-construction estimates were also planned; however, construction did not occur in time. Population data from the two zones can be compared since species compositions and stream flows (Table 8, stations 6 and 7) are similar.

Section 14 (UA) had the highest average trout populations, exceeding those of sections 12 and 13 (PA) by 35 and 81 percent, respectively. The number of trout greater than 18 cm was significantly higher in section 14 compared to sections 12 and 13 (Table 9). The standing crop biomass (Figure 2) was also significantly higher, exceeding sections 12 and 13 by 88 and 103 percent, respectively.

Sections 12 and 13, however, had a significantly higher whitefish biomass and total gamefish biomass in 1975 (Figure 3), even though section 14 contained more trout. The biomasses of gamefish in sections 12 and 13 were 90 and 52 percent higher, respectively, than the biomasses in section 14.

Fish populations in zones IV and V are characterized by relatively large numbers of whitefish and few cutthroat trout. Rainbow and brown trout effectively replace cutthroat numbers in these lower zones (Table 9).

#### FISHERMEN SURVEY

Fishing pressure counts were made during the summers of 1974 and 1975 on the St. Regis River (Table 10). The fishing season runs from the third Saturday in May through November on this river. Pressure counts were made during the period when fishing was heaviest (July and August). High water in late May and June discourages fishing at this time. Little fishing occurs during the fall hunting seasons.

# Pressure Counts

Estimated total fishing pressure went from 3682 hrs in 1974 to 5207 hrs in 1975, an increase of 41 percent. This is equal to a pressure of 65.7 hrs/km and 92.8 hrs/km in 1974 and 1975, respectively. Approximately 52 percent of the fishing occurred on weekends and holidays, even though these days equaled only 31 percent of total days. Zones IV and V (47 percent of censused length) received 68 and 51 percent of the total fishing pressure in 1974 and 1975, respectively. A stocking program, which ended with the 1973 plant, may have stimulated the increased fishing pressure in these zones. The highest fishing pressure (200 hrs/km) during the two years was recorded on sections 12 and 13 in zone IV (Table 10). Unaltered sections (Table 10) showed 57 percent greater fishing pressure than the altered sections for the first three zones (mean of 1974 and 1975).

#### Creel Survey

A limited creel survey of fishermen in 1975 showed a catch rate of 0.85 fish/hr. Species composition of fish creeled was as follows: cutthroat trout - 56 percent, brook trout - 25 percent, rainbow trout - 10 percent, brown trout - 3 percent, dolly varden - 1 percent, and mountain whitefish - 5 percent. Average total length of trout creeled was 20.6 cm (range, 13.2 - 33.7 cm). Mountain whitefish averaged 36.1 cm in total length. The average weight of trout creeled was 78 g, compared to 451 g for the mountain whitefish. Due to the small size of the trout, many were caught and released by the fishermen.

Approximately 64 percent of the fishermen were from out-of-state, with 33 percent coming from the adjacent parts of northern Idaho. Average length

TABLE 10. ESTIMATED FISHING PRESSURE OBSERVED ON THE ST. REGIS RIVER FOR TWO PERIODS DURING THE SUMMERS OF 1974 AND 1975.

		hrs/km				hrs/km	
Zone	Nonstudy Areas	Study Sect Altered* Ur		Nonstud Area		Study Altered	Sections Unaltered
			1974		# C		
		July 1-31			Aug.	1-Sept.	2
I v	26	74	24	14		0	0
II .	33	0	23	17		0	30
III	21	31	27	21	*	0	0
IV	34	, <del></del>	103	36	*:	11 = ====	39
V Ave.	66	36	<u>55</u> 58	53 31			<u>16</u> 19
						n 2 <sub>2</sub>	
			1975			, O	21 21 N
		July 1-31	* =	y 0	Aug.	1-Sept.	1
I	66	32	70	42		66	26
II	46	130	178	32		0	0
III	39	10	79	21		44	84
IV	47		128	28		<u></u> ,	130
V Ave.	<u>38</u> 46	39	41	45		<del></del> 41	125 92

<sup>\*</sup> Both old and newly altered sections.

Both unaltered and partially altered.

of each day's fishing was 2.7 hrs. Types of bait used was divided evenly between flies and live bait (46 percent each), with the remainder comprised of lures or a combination of baits.

# SECTION V

Physical, chemical and biological factors are all important in the creation and maintenance of good trout habitat. Altering any of the above factors may be detrimental to a given trout population.

The chemical makeup of the water in the St. Regis River is dependent upon the substrate and geological makeup of the drainage. Chemical changes caused by the new channel alterations were not detectable throughout the course of this study. Changes in the water chemistry are probably long-term, gradual changes caused by the accumulation of channel alterations over the years.

The physical changes caused by channelizations and alterations are readily detectable. Differences were shown in sinuousity, pool-riffle periodicity and the variations in depth, width and water velocity between altered and unaltered sections. "Old" channelizations as noted both by Bayless and Smith and in this study do not readily return to an unaltered meandering condition unassisted. Stabilizing one of the banks with riprap is sufficient to prevent any stream meandering over a long period of time (50 years or more).

Newly altered sections with mitigating structures caused the thalweg to move back and forth across the channels and created bottom contours which approximated unaltered conditions. In 1974, a year after the mitigating structures in sections 7 and 8 were completely installed, cutthroat trout numbers increased dramatically (Table 11, Appendix). The stepdams placed in section 2 were less successful in restoring trout habitat. The flood in 1974 destroyed most of these dams, turning them into a random rock arrangement. Some of the jetties in section 8 were also lost during this high water, which points to the need for better engineering and placement of such structures.

The loss of vegetative bank cover was complete along most of the newly altered sections. The importance of overhanging bank cover along small streams was

demonstrated by Hunt and Boussu 4. The large amount of riprap used along the newly altered sections of the St. Regis did provide some bank cover for trout.

No single physical parameter measured during this study was well correlated with the trout or whitefish populations. The number of pools per section as measured by pool riffle periodicity provided the best correlation to trout populations ( $\mathbf{r} = 0.49$ ). A combination of the many interrelated parameters probably best describes the change in fish populations caused by channelization.

Sections 7 and 8 showed sharp increases in numbers and biomass of trout after mitigating devices had been in effect for one year. In 1974 and 1975, the biomass of trout in section 7 increased by 89 and 207 percent, and in section 8 by 175 and 173 percent, respectively, over 1973 levels. During this same period, trout populations were decreasing or remaining stable in the unaltered, partially altered and "old" altered sections in zones I and II. Increased numbers of age I and II cutthroat trout in sections 7 and 8 (Table 12, Appendix) accounted for the higher biomasses recorded.

Estimates of trout population in the lower two zones were probably low because of harvest by sport fishermen prior to electrofishing operations. Estimates were not made until late August each year after much of the pressure had occurred. This fact must be considered if estimates made after I-90 construction are to be compared to baseline data gathered here. Fishing had little effect on the population comparisons made in the upper zones because most of it occurred after the estimates were made each year.

#### SECTION VII

#### REFERENCES

- 1. Alvord, W., and J.C. Peters. Channel changes in thirteen Montana streams. Montana Fish & Game Dept. Helena, Montana. 1963. 23 p.
- 2. Elser, A.A. Fish populations of a trout stream in relation to major habitat zones and channel alterations. Trans. Amer. Fish. Soc., 97(4): 389-397. 1968.
- 3. Irizarry, R.A. The effects of stream alterations in Idaho. Idaho Fish and Game. Boise, Idaho. Job Comp. Rep. Project F 55-R-2. April 1960. 26 p.
- 4. Congdon, J.C. Fish populations of channelized and unchannelized sections of the Chariton River, Missouri. Dept. of Fish Mgt. Jefferson City, Missouri. 12 p.
- 5. Tarplee, W.H. Jr., D.E. Louder, and A.J. Weber. Evaluation of the effects of channelization of fish populations in North Carolina's coastal plain streams. North Carolina Wildlife Resources Commission. Raleigh, N.C. 1971. 22 p.
- 6. Hunt, R.L. Responses of a brook trout population to habitat development in Lawrence Creek. Dept. of Nat. Res., Madison, Wisconsin. Tech. Bull. No. 48. 1971. 35 p.
- 7. Shetter, D.S., O.H. Clark, and A.S. Hazzard. The effects of deflectors in a section of a Michigan trout stream. Trans. Amer. Fish. Soc., 76: 248-278. 1946.
- 8. Latta, W.C. The effects of stream improvement upon the anglers' catch and standing crop of trout in the Pigeon River, Otsego County, Michigan. Michigan Dept. of Nat. Res. Research and Development Report No. 265. May 1972. 57 p.
- 9. Barton, J.R., D.A. White, P.V. Winger, and E.J. Peters. The effects of highway construction on fish habitat in the Weber River, near Henefer, Utah. Bur. Reclam. Rep. REC-ERC-72-17. June 1972. p. 17-28.
- 10. Ricker, W.E. Handbook of computations for biological statistics of fish populations. Fish. Res. Bd. Can. Bull., 119: 1-300. 1958.
- 11. Snedecor, G.W., and W.G. Cochran. Statistical methods, sixth ed. Ames, The Iowa State Univ. Press. 1967. p. 62.
- 12. Leopold, L.B., M.G. Wolman, and J.P. Miller. Fluvial processes in geomorphology. San Francisco and London, Freeman and Co. 1964. 522 p.

13. Bayless, J., and W.B. Smith. The effects of channelization on the fish populations of lotic waters in eastern North Carolina. North Carolina Wildl. Resource Comm. Raleigh, N.C. 1964. 15 p.

legal a desta de la la la companya de la companya

14. Boussu, M.F. Relationship between trout populations and cover on a small stream. Jour. Widl. Mgt., 18(2): 229-239. April 1954.

# SECTION VIII

APPENDIX

(RB = RAINBOW TROUT, CT = CUTTHROAT TROUT, EB = BROOK TROUT, LL = BROWN TROUT, DV = DOLLY VARDEN TROUT AND WF = MOUNTAIN WHITEFISH.) [CONFIDENCE INTERVALS AT 80% LEVEL.] ESTIMATED NUMBER AND BIOMASS OF GAMEFISH PER 1000 METERS OF STREAM IN EACH SECTION OF THE ST. REGIS RIVER IN 1973, 1974 AND 1975. TABLE 11.

WF		1	-	) 0.5		-	) 2.0		-	) 5.1		-	) 5.9		+	16.9
Biomass (kg) B Total (±)		29.2(1.3)	15.7(2.7)	19.3(2.1)	21.3(1.0)	17.1(2.1)	18.8(1.3)	33.4(2.6)	18.6(2.1)	23.9(3.8)	24.5(2.2)	12.5(2.2)	9.5(1.4)		18.9(3.5)	19.4(3.0)
Bion	e e e	11.1	4.4	4.6	5.1	3.6	5.5	17.0	10.0	6.1	11.5	7.4	5.4		8 8	7.6
៩		18.1	11.3	14.7	16.2	13.5	13.3	16.4	8.6	17.8	13.0	5.1	4.1		10.1	11.8
WF		- 1	1	2	107	Ī	7	• 1	T	10		- 1	15		T	39
cm and over Total (±)		181(12)	58(13)	(2)09	139(6)	31(9)	(6)67	175(12)	26(6)	72(15)	129(10)	40(10)	26(9)		84(15)	(8) (24)
18 EB	Zone I	71	10	4	38	<b>∞</b>	15	91	27	16	67	19	15	Zone II	42	26
CT.	02	110	8 7	26	101	23	34	84	29	26	78	21	11	20	42	43
WF		- 1-	1	7		-	4	17. No.	l	10	l	- 1 - 1	15		į 1	39
Number Total (±)		Partially altered control. 1973 506 94 600(40)	598(131)	615(63)	517 (38)	886(126)	610(51)	641 (116)	(66) 799	643(113)	278(39)	437 (83)	244 (38)		404 (78)	470(80)
EB		1 con 1 94	192	117	adder 61	161	154	1 142	331	156	119	284	136		1* • 50	163
5		altered 506	406	498	tepdams 456	725	456	contro 499	333	487	ered 159	153	108		contro 354	307
Section Year	2.	artially 1973	1974	1975	Altered/stepdams added 1973 456 61	1974	1975	Unaltered control	1974	1975	"Old" altered	1974	1975		Unaltered control* 1973 354	1975
Sectio		1. Pa			2. A1			3. Un			4. "0				5. Un	

TABLE 11. CONTINUED.

												~							Č.
	WF		1	11.4		1	1	33.0	17.5	- 1	1	17.8		- 4	- 1	0.4	- 1	- 1	10.2
3	(±)	6	17			3.1)	(9.9	(6.1		2.8)	3.0)	(0.4		3)	5.7)	3.3)	3.6)	2.6)	
Blomass (kg)	$\operatorname{Total}_{(\pm)}$	30 6(5 9)	28 8(7 7)	21.7(3.5)		15.3(3.1)	28.9(6.6)	47.0(4.9)	18.2(2.4)	19.4(2.8)	53.3(8.0)	53.0(4.0)		10 2/2 3	28.7(6.7)	17.9(3.3)	32.1(8.6)	16.7(2.6)	16.3(2.3)
omas									240					15					
B1	EB	0				2 6.1	5 5.4	8.8	1 6.1	2 7.2	1 13.2	0.21		10		5 5.3	14.6 17.5	5 9.1	3 6.0
3	TJ.	7 6	25.4	180		9.2	23.5	38.2	12.1	12.2	40.1	38.0			14.8	12.6	14.	7.6	10.3
	WF		- 1	77	11=21		ļ.	84	52	= 1	1	20		#T		2		- 1	39
No. 18 cm and over	Total(±)	136(22)	54(7)	85(21)		70(16)	99(34)	255(42)	87 (23)	67(12)	72(14)	305(30)		88(0)	71(18)	94(28)	157 (54)	55(9)	111(22)
. 18 cm	EB T	15	15	24	i	24	10	36	33	14	47	20	Zone III	77	41	37	78	25	41
No	CT	8	36	6 6	1	94	88	219	54	53	25	255	Zon	77	30	57	79	30	70
	WF	1		77		ı	4	84	52	1	1	20			1	7	- 1		39
Number	Total(±)	11.	1212(370)	542(81)		led. 276(94)	920(269)	836(100)	380(72)	810(138)	2293(372)	1018(92)		(78)007	770(299)	657(100)	744 (183)	423(82)	301(41)
N.	EB	control	100	39		ks add 43	103	72	57	lded. 197	216	29		115	119	09	control 243	167	62
1	CT	ltered 879				dom roc 233	817	164	323	ties added 613 197	2077	951		red.	651	597	ltered 501	256	239
	on Year	Partially altered	1974	1975		Altered/random rocks added. 1973 233 43 27	1974	1975	7A. Altered. 1975	Altered/jetties added. 1973 613 197	1974	1975		"Old" altered.	1974	1975	Partially altered 1973 501	1974	1975
	Section	6. P				7. A			7A. A	8 •				.6			10. P		

0mass (kg) LL DV 0.9 2.2 6.9 4.7 0.8 3.4 1.7 6.9 4.3 1.3 2.3	0.3. 5.3 40.2 1.0 56.2(6.5) 0.1 2.8 20.5 0.8 30.8(5.1)	1.4 14.0 0.9 19.2(3.6) 21.5
lomass (kg)  LL DV Total(±)  8.9 25.3(4.8)  0.9 13.1(1.4)  2.2 11.8(2.0)  11.9 23.5(5.3)  6.9 13.2(2.9)  4.7 0.8 16.4(2.5)  3.4 1.7 11.5(2.1)  6.9 32.0(2.2)  4.3 1.3 13.3(2.0)  2.3 7.9(1.8)	5.3 40.2 1.0 2.8 20.5 0.8	6.0
LL DV (8.9 0.9 6.9 6.9 4.7 0.8 3.4 1.7 6.9 4.3 1.3 2.3	5.3 40.2 1.0 2.8 20.5 0.8	6.0
LL DV (8.9 0.9 6.9 6.9 4.7 0.8 3.4 1.7 6.9 4.3 1.3 2.3	5.3 40.2 2.8 20.5	1.4 14.0 0.9
LL LL 11.9 8.9 8.9 6.9 6.9 6.9 6.9 6.9	5.3 40.2 2.8 20.5	1.4 14.0
B10 6.1 6.1 6.1 5.2 5.2 6.3 3.5 0.6 0.6	2.3	1.4
	0.3. 0.1	
	0	4
		0.4
RB 0.1 0.1 1.6 0.1 1.4 1.4 1.4 5.4 5.4	9.4	2.5
224 224 2111 204 204 168		53
l over Total(±) 81(23) 92(10) 71(13) 60(10) 7 105(10) 46(7) 50(9) 114(8) 32(5) 21(9)	170(23) 62(9)	70(12)
1 0v 1 10t 10t 10t 10t 10t 10t 10t 10t 10t 1	170	70
cm and over  L DV Total  0 81(2 2 92(1 4 60(1 4 60(1 7 60(1 7 105(1 8 5 46(7 8 5 50(9 9 114(8 6 8 32(5 1 21(9 7 21(9 7 21(9 7 21(9 7 21(9 7 21(9 7 70 114(8 7 70 114(8 7 70 114(8 7 70 114(8 7 70 114(8 7 70 70 114(8 7 70	3	
18 c 11 10 10 12 2 2 2 2 2 2 2 2 2 2 2 2 2 2	36	45
	34	7
112 12 22 22 22 22 22 22 22 22 22 22 22	۳ ا	m
RB 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	44 8	14
225 225 211 211 190 170		53
(46) 5(13) 5(13) 3(14) 3(13) 3(64) 9(16) 2(13) 4(37) 9(19)	(33)	20)
Total 221(9 1119(1 107(2 247(4 85(3 333(6 99(6 142(6 214(7)	279(33) 381(83)	128(20)
DD	7	-
Number LL 13 2 2 34 14 17 60 60 16 43 11	116 115	47
	67	79
red. 55 55 35 add 35 8 add 24 24 29 32 32 29 29 29 29 29 29 29 29 29 29 29 29 29	ر و	4
AB CT altered.  8 55 2 35 2 35 2 35 2 35 3 12 3 12 115 29 119 32 altered. 122 7 140 2 63 2	. 88 .05	20
Year RB ially alt 1973 red. 8 1975 2 1975 2 1974 2 1974 2 1975 3 1974 115 1975 1975 1975 1975 1975 1975 1975	1973 88 1974 205	1975
	19 19	19
Section  11. Par  111. Alt  111. Alt  12. Par  13. Par  14. Una		
Sect. 111. 111. 111. 111. 113. 12. 14.		

\* 1973 "Section five" moved 1.6 km upstream in 1975.

ESTIMATED POPULATION AND AVERAGE LENGTHS BY AGE GROUPS GIVEN FOR YEARS 1973-1975. (AGE AS OF LAST ANNULUS; IV<sup>+</sup> = 4 AND OLDER FISH) TABLE 12.

Ave.	1				
WF 75					· · ·
Ave. (Lt)					
Brown Trout					
Ave. (Lt)	-				
out 75	ħ.				
w Tr	101		e le v		. /1 /
Rainbow Trout	957				
	H		14		660
Ave. (Lt)	Zone	(11) (17) (26) (36)	(£25) (£25)	(11) (17) (26) (28)	(12) (16) (26)
out 75		13 96 4 0	29 123 0	34 118 4 0	32 97 5
Brook Trout	54 32	159 28 4 0	145 10 6 0	263 49 16 2	234 46 3
Broc 73	7	21 46 24 2	24 ] 4 0	7 7 7 7 8 7 8 7 8 9	70 2 9 35
Ave. (Lt)	S.	(10) (16) (22) (26)	(10) (16) (22) (26)	(10) (16) (23) (26)	(10) (23) (23)
	×	5588	5555	5555	5555
Trou 75		244 242 7	added. 204 238 0	180 279 15 8	65 4 0
roat 74		284 284 99 18	- m c w c	rol. 234 81 12 4	120 16 2
Cutthroat Trout 73 74 75		294 294 149 39 24	tepdar 278 125 42 11	control 364 234 82 81 28 12 25 4	• 27
Age	120	ally 2 1 1 ‡	ed/st	m	alte
	1, 1	Partially altered I 294 284 II 149 99 III 39 18 IV <sup>†</sup> 24 5	Altered/stepdams	Unaltered I II III IV <sup>†</sup>	"blo" I III III
Section	•	i	2. A	з. п	4.
		g = 5 c - 0%			

TABLE 12. CONTINUED.

Ave. (Lt)		(25) (34) (34) (38) (38)	(26) (36) (36) (36)	(25) (33) (33) (33)	3 (3 (3 (3 (3 (3 (3 (3 (3 (3 (3 (3 (3 (3
WF 75		26 5 5	33330	0 2 29 119 41	0 0 31 10 10
Ave. (Lt)			a 10 4 5		
Trou	81 .		*II		85
Brown Trout 73 74 75					* x - 2
73-40	No.		entin e sa		
Ave. (Lt)	#31 		5 5 = 5 = 2 × 5		
out 75				- e = 123	
Rainbow Trout					
afnbc 73	0 an - 12 an				1 97.
5 9 11	ij				
Ave. (Lt)	Zone	(11) (16) (25) (31)	(12) (19) (25) (32)	(13) (18) (25) (32)	(11) (18) (23) (36)
out 75		42 109 7 2	2 7 4 5 8	51 8 6	4 33 17 2
Brook Trout 3 74 75	3 4	1111	79 16 2 2	73 20 8	e a se
Broc 73		9 11 11	16 29 23 2	17 8 11 8	
Ave. (Lt)	a a	(10) (16) (23) (26)	(10) (16) (23) (26)	(10) (17) (23) (28)	(9) (16) (22) (31)
15 12					
Trou 75		96 195 7 4	179 255 23 0	rocks added 375 229 218 506 24 23 0 6	116 191 14 3
roat 74	×2 = 5		164 328 14 5	U I CV	
Cutthroat Trout 73 74 75	200	283 44 13 13	alte 702 119 43 16	Altered/random	
Age	,	H+	111	ed/re	e H+
1 -1	The Tered	II III IV <sup>†</sup> V <sup>†</sup>	artía I III III IV <sup>†</sup>	itere I II III IV V	Altered. I II III IV+ V+
Section		•	• P	7 ·	7A. A

TABLE 12. CONTINUED.

	Ave. (Lt)		(24) (24) (33) (37)	146 2			a a	(24) (24) (33) (38)
	WF 75		0 3 11 17			00000		0 12 15 7
	Ave.			e E:				
	Brown Trout							
	Ave. (Lt)		a a a					
	Rainbow Trout 73 74 75						87	
	Rainbo 73	i i i i i i i i i i i i i i i i i i i	9 3 mm					= 2 6 <sup>(2)</sup>
	Ave. (Lt)		(13) (18) (24) (32)	Zone III		(13) (20) (26) (31)		(13) (20) (24) (31)
	cout 75	= 23	18 18 18	2		34 8 0		18 38 4 1
100	Brook Trout		138 53 12 12	(8 (8)	s	74 13 30		133 21 3 8
	Brc 73		177 9 10 0			66 28 9 11		146 63 18 15
	Ave. (Lt)		(10) (17) (23) (28)			(10) (17) (24) (29)		(10) (24) (24) (29)
2	Cutthroat Trout Ave. 73 74 75 (Lt)	dded.	408 499 41 3			472 118 7 0	6	151 81 5
	roat 74	es a	1656 416 6			504 134 11 3	tered	182 66 5 3
		/jett/	494 1656 4 110 416 9 0 0		ltered	244 44 18 8	ly al	375 105 15 6
	Age	1	11111		"Old" altered.	THE TATA	Partially altered.	1 111 111 104 14
	Section	8. AI			9. "0		10. Pa	

TABLE 12. CONTINUED.

	1	-	~	~		_			~ .	~~	_		_			_	_			_		_	-	_
Ave. (Lt)		1	(26	(28	(34)	(38	7		(25	(34)	(37		(17	(24	(28	(34)	(37			(20	(26)	(30	(35)	(39
WF 75		-	1 6	125	53	27		0	H	61	94		m	7	40	94	76			~	41	51	54	26
Ave. (Lt)	e(	3	(24)	(36)	(42)	(21)			(23)	(35)			(13)	(23)	(35)	(42)	(67)			(13)	(22)	(38)	(43)	(41)
out 75		C	· -	0	. н с	0		0 ,	⊣ 、	<b>5</b> ⊢			0	<b>∞</b>	Н	7	ന			-	13	Н	н	0
Brown Trout				Ť									22	H	М	10				51	5	7	7	0
Brow 73	1 1 2	2	ı	. 7	νc	<b>1</b>	-		8											'n	Н	0	6	1
Ave. (Lt)		(13)	(24)	1			\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	(T4)					(16)	<u> </u>	Ĵ	(36)				(13)	(23)	(29)	1	
out 75		-	_	0	0		f e	<u>.</u>	<b>⊣</b> ç	0			ო	0	0	0				13	2	1	0	
Rainbow Trout 73 74 75													Н	0	0	н	2.	Λ		110	က	7	0	
1nbo 73	2 _	0	0	0	0													IV &			10	53	0	
Ra	a) 1																						3.	
Ave. (Lt)	5).	(14)	(19)	(25)	(30)		3	(13)	(26)		0		(14)	(20)	(25)	(32)		Zones	0.	(14)	(20)	(22)	(29)	
out 75	(1975)	4	43	7	0		9	07	<b>0</b> -	10			17	32.	9	Н				5	19	9	0	
Brook Trout	red												95	46	12	0				85	31	9	7	
Broc 73	altered	65	29	15	11			ě												21	0	က	က	
we. (Lt)	& 11U	1	6	24)	(6:		- (	i F	9	36)			(7)	17)	(4)	5				(2)	19)	()	(9	
it Av	i i	$\Box$	C	S	C		5	3,5					C	C	2	$\mathbb{C}$				C	C	2	<u> </u>	
Trou 75	(197	14	36	7	Н :		added.	20	2 ~	7		5	2	5	-	Н			î	28	က	0	н.	
oat 74	red		4									rol.	32	21	2	Ţ			red	19	œ	Н	0	
Cutthroat Trout Ave.	alte	23	21	2	7		STITE					control							altered	13	10	П	П	
Age	111y		_	냂	٠ <u>.</u>	-	3d/]e		. :	!t	1.	red			∐-	Ł.			111y	12		<u>H</u> -	t.	
1	Partially altered (1973)	ěН	F	F	i b		Altered/jettles	Ŧ	;	¦ À·	5	Unaltered	H	I	İII	≥‡	>		Partially	H		ij	<b>≥</b> ţ	>
Section	P						. A		05%	, 2		1. Ur.	10											
Sec	Ħ				224	į	77					11A.							12.					

TABLE 12. CONTINUED

		Cutth	roat	Trou	Cutthroat Trout Ave.	Broc	k Tr	cout	Brook Trout Ave.	Rain	] MOC	Rainbow Trout	Ave.	Bro	Brown Trout	rout	Ave.	WF	WF Ave.
Section Age 73 74 75	Age	73	74	75	(Lt)	73	73 74 75	75	(Lt)	73 74 75	74	75	(Lt)	73	73 74 75	75	(Lt)	75	(Lt)
	,		4	ķ						ō					ly.	2.0	1		
13. Partially altered.	tfall	y alt	ered																
	H	0	0	<b>-</b>	(12)	Ö	17	0	(13)	37	129		(15)	Н	37	0	(14)	11	(20)
	II	-	0	Н	(18)	-	4	က	(20)	18	9	12	(24)	0	Н	6	(24)	33	(25)
	III	S	7	Н	(22)	Н	0	0	(56)	16	2		(30)	1	က	7	(31)	47	(30)
	ţ.	1	0	0	(27)	-1	0	0	(30)	5	0		(37)	7	7	0	(42)	77	(32)
	ł A													0	Н	<b>-</b>	(42)	37	(37)
14. Unaltered control.	ltere	d con	trol													ia -			
	H	Н	7	ᆸ	(13)	23	28	10	(14)	28	196		(14)	36	80	7	(14)	0	1
	II	Н	Н	7	(18)	34	10	15	(13)	14	<b>∞</b>		(22)	17	က	28	(23)	ന	(26)
	III	7	0	-	(56)	œ	7	Н	(22)	15	7	0	(30)	30	10	7	(33)	17	(30)
	ţ.	0	0	0	$\widehat{\mathbb{L}}_{q}$	7	0	0	(53)	1	0		(32)	29	20	11	(40)	12	(32)
	\$													4	က	က	(41)	24	(33)





As the Nation's principal conservation agency, the Department of the Interior has basic responsibilities for water, fish, wildlife, mineral, land, park, and recreational resources. Indian and Territorial affairs are other major concerns of America's "Department of Natural Resources."

The Department works to assure the wisest choice in managing all our resources so each will make its full contribution to a better United States—now and in the future.